

C
C I/O : (C*3) USREXT = USREXT UNDER WHICH ADAS DATA IS STORED
C (IF BLANK DEFAULTS TO DEFEXT)
C
CA (C*8) DEFGRP = PARAMETER = DEFAULT USER GROUP FOR ADAS
C DATA SOURCE
C
CA (C*80) DEFTYP = PARAMETER = DEFAULT USER TYPE FOR ADAS
C DATA SOURCE
C
C (C*3) DEFEXT = PARAMETER = DEFAULT USER EXTENSION FOR ADAS
C DATA SOURCE
C
CA (C*8) ADASGR = CURRENT ADAS DATA SOURCE GROUP
C
CA (C*80) ADASTY = CURRENT SUB-DIRECTORY NAME (OPTIONAL)
C
C (C*3) ADASEX = CURRENT ADAS DATA SOURCE EXTENSION
C
C

C ROUTINES:

ROUTINE	SOURCE	BRIEF DESCRIPTION

C NOTE:

C TO CHECK CURRENT ADAS SOURCE USRGRP, USRTYP AND USREXT
C CALL XXSSXB WITH '?' AS INPUTS.
C

C AUTHOR: HUGH P. SUMMERS, JET
C K1/1/57
C JET EXT. 4941
C

C DATE: 2/09/93
C

C UPDATES: 24/10/94 L. JALOTA (TESSELLA SUPPORT SERVICES PLC)
C CHANGED VALUES OF DEFGRP, DEFTYP, DEFEXT SUITABLE
C FOR DEC ALPHA DIRECTORY STRUCTURE.

C UPDATE : 22/11/94 L. JALOTA - TIDIED UP CHARACTER LENGTH DEFINITIONS.
C

C-----
CHARACTER*3 USREXT
CHARACTER*8 USRGRP
CHARACTER*80 USRTYP