## **ADAS Subroutine xxnbbf**

```
SUBROUTINE XXNBBF ( NCAP7 , LAMDA , C , X ,S , IFAIL )
С
C
C-
С
С
 PURPOSE: Evaluates a cubic spline from its B-spline representation
С
C CALLING PROGRAM: VARIOUS
С
C SUBROUTINE:
С
C INPUT: (I*4) NCAP7
                            = NBAR+7, where NBAR is the number of
С
                               intervals (one greater than the number
С
                               of interior knots, i.e. the knots
С
                               strictly in the range LAMDA(4) to
С
                               LAMDA(NCAP+4)) over which the spline
С
                               is defined.
С
                               CONSTRAINT: NCAP7 >= 8
С
С
 INPUT: (R*8) LAMDA()
                            = Values of the complete set of knots
                               LAMDA(J), J=1, NBAR+7.
С
С
                               CONSTRAINT: Must be in non-decreasing
С
                               order with LAMDA (NCAP7-3) > LAMDA (4).
С
С
 INPUT: (R*8) C()
                            = The coefficients of the B-spline N_i(x),
С
                               for i=1,2,..., nbar+3. The remaining
С
                               elements (from NBAR+4 to NBAR+7) are not
С
                               used.
С
C INPUT: (R*8) X
                            = The argument x at which the cubic spline
С
                               is to be evaluated.
С
                               CONSTRAINT:
С
                                  LAMDA (4) \leq X \leq LAMDA (NCAP7-3)
C INPUT: (I*8) IFAIL
                            = 0 : stop if any error
С
                            = 1 : continue if non-fatal error.
С
                           = The value of the spline, s(x)
C OUTPUT: (R*8) S
С
C OUTPUT: (I*4) IFAIL
                            = 0 : no error detected
С
                             = 1 : X does not satisfy
С
                                    LAMDA(4) \leq X \leq LAMDA(NCAP7-3)
С
                             = 2 : NCAP7 < 8
С
С
С
           (I*4) KL
                            = GENERAL INDEX
С
                            = GENERAL INDEX
           (I * 4) KU
С
           (I \star 4) K
                            = GENERAL INDEX
С
           (I * 4) J
                            = GENERAL INDEX
           (R*8) E1
С
                            = GENERAL REAL
С
                            = GENERAL REAL
           (R*8) E2
С
C ROUTINES: NONE
```

```
С
C AUTHORS: H. P. Summers and A. C. Lanzafame, University of Strathclyde
C DATE: 11 January 1995
С
C UNIX-IDL PORT:
C VERSION: 1.1
                               DATE: 22-1-96
C MODIFIED: TIM HAMMOND (TESSELLA SUPPORT SERVICES PLC)
       - PUT UNDER SCCS CONTROL
С
С
C VERSION: 1.2
                               DATE: 06-07-2004
C MODIFIED: Allan Whiteford
            - Changed name from dxnbbf to xxnbbf
С
C-----
                    IFAIL, NCAP7
C(NCAP7), LAMDA(NCAP7),
    INTEGER
    REAL*8
                                                   S
    REAL*8
                    X
```